



## LED POST-TOP AREA LIGHTS



The images are merely illustrative, some technical features and accessories may be changed without notice.



October 2020

## Product Description

This Post Top Luminaire is a sleek, specification-grade solution for lighting pathways, parking areas, gardens and other outdoor spaces.

It can be specified in 50W, 75W, 100W & 170W, and is capable of replacing HID fixtures ranging from 175W - 400W. It can be used efficiently on pathways as well as parking lots or general areas.


## Key Features

- **Super Bright LED**
- **100-277Vac 50/60Hz Universal Voltage Driver**
- **Wet Location Rated for Outdoor Use**
- **Replaces HID/MH 300~400W**
- **5 Years Limited Warranty**
- **Photocell Optional**

## Product Specifications

<b>LED Type:</b>	SMD LED
<b>Power consumption:</b>	Up to 100W ±5%
<b>Input voltage:</b>	100-277Vac 50/60Hz
<b>Efficacy:</b>	Up to 130 lm/W
<b>P.F.:</b>	>0.95
<b>CRI:</b>	85
<b>Beam Angle:</b>	120°
<b>Material:</b>	Aluminum die-casting heat sinks and frost cover
<b>Beam angle:</b>	130°
<b>IP rating:</b>	IP67
<b>Operating Temperature:</b>	-40 to +45 C°

## Product Measurement






## Ordering Guide

Example: PTALS50M130F41

Type	Dimmable Non-dimmable	Watts	Voltage/Driver	Efficacy	Cover	CCT
<b>PTAL</b>	<b>S</b>	<b>50</b>	<b>M</b>	<b>130</b>	<b>F</b>	<b>41</b>
<b>PTAL</b>	<b>S</b> <b>P</b>	Non-Dimmable Dimmable	<b>30</b> 30W <b>50</b> 50W <b>75</b> 75W <b>100</b> 100W	<b>M</b> Internal 100-277V 50/60Hz	<b>130</b> 130lm/W	<b>F</b> Frost <b>27</b> 2700K <b>30</b> 3000K <b>41</b> 4100K <b>50</b> 5000K <b>57</b> 5700K




## Luminous Intensity Distribution





# Teslights+



**World Headquarters**

4000 Montgomery Dr.

Suite L3

Santa Rosa, CA 95403, USA

+1 707 536 5467

[www.teslights.com](http://www.teslights.com) - [info@teslights.com](mailto:info@teslights.com)