

The images are merely illustrative, some technical features and accessories may be changed without notice.



For additional information, please contact us **www.teslights.com - info@teslights.com** 







# **Product Description**

1

The Teslights Smart LED Streetlights C have been designed and manufactured in order to meet the lighting demand of narrow environment, thanks to a lens that could produce a rectangular lighting pattern.

These luminaires are suitable to be used in the middle of the narrow streets, since rectangular lighting distribution can reduce dark spot between two fixtures, make full use of light and have better lighting uniformity for the lighting environment.

Light in weight and small in size, it has a special-designed bracket which allows to easily and firmly install on wire rope crossing roadway or streets and be perfectly integrated with surrounding environment.

While reducing maintenance costs and improving performance, the superior quality output of the Teslights Smart LED Streetlights C deliver immediate modernization in illumination.

## **Key Features**

- Anodized Aluminum heat sink
- Modular manufacturing process
- 5 year factory warranty
- No rewiring of fixture, minimizing replacement and maintenance costs





LED package:
Power consumption:
Input voltage:
Efficacy:
THD:
P.F.:
CRI:
Dimming:
Material:
-

Beam angle: IP: Operating temperature: SMD 3030 Up to 90W 100-277Vac 50-60Hz Up to 130 lm/W±5% <18% ≥0.92 >80 0-10V 6030 aluminum alloy and PC cover 120°C IP66 -40°C+45°C



### **Product Measurement**





Model	Measures (AxBxCxD)
SLC 30W / 60W / 90W	330 x 180 x 186 mm

ghting ting





#### Example: SLCP60M130C40

Туре	Dim or Non-Dim				Driver/Power				Cover		ССТ	
SLC							130					
SLC	Р	Dimmable	30 60	30 W 60 W	М	Internal 100~277VAC	130	130 lm/W	с	Clear	27 30 40	2700 K 3000 K 4000 K
			90	90 W	-		120	120 lm/W			50 55 65	5000 K 5500 K 6500 K

# Teslights+

World Headquarters

4000 Montgomery Dr. Suite L3 Santa Rosa, CA 95403, USA +1 707 536 5467 www.teslights.com - info@teslights.com